

ZXP Series 3™ Card Printer



Best-In-Class Choice for Desktop Card Printing

The ZXP Series 3 direct-to-card printer offers several advanced features that provide best-in-class performance at an affordable price point. Zebra's ZRaster™ host-based image processing technology, for example, enables high-speed printing while optimizing image quality. And Zebra is first to market with high-performance ribbons that have an improved formulation specifically designed for high-speed, high-quality printing.

The ZXP Series 3 slips easily into tight work spaces thanks to its compact footprint, and with easy-to-use attributes like quick-replace Load-N-Go™ ribbon cartridge and LCD display with operating prompts, it requires little training and optimizes uptime. Meet a spectrum of applications with a full suite of buy-now or add-later encoding options, and a choice of connectivity for easy system integration.

Print one or both sides with high-quality, consistent, color or monochrome images for a variety of applications including ID and access control cards, and personalized gift, membership and loyalty cards. For affordable printing of financial cards, just select the enclosure lock option.



ZXP Series 3 Printers Offer:

- ZRaster™ host-based image processing technology for increased throughput and image quality
- Smart card and magnetic stripe encoding to meet a variety of markets and applications
- New high-performance ribbons designed for high-speed, high-quality image printing
- Intuitive design for ease of use and simplified training requirements
- Optional enclosure lock for financial card printing
- Single- or dual-sided direct-to-card printing



Specifications at a Glance*

Printing Specifications

- Dye sublimation thermal transfer direct-to-card
- ZRaster host-based image processing technology
- Full-color or monochrome printing
- Single- and dual-sided printing
- 750 cph monochrome single-sided
- 180 cph full-color YMCKO single-sided
- Edge-to-edge printing on standard CR80 media

NOTE: Print speed based on click to drop, average print coverage, with USB connectivity, and cards per hour (cph) under certain conditions. Print speeds subject to change.

General Specifications

- Zebra True Colours® ix Series™ high-performance ribbons with intelligent media technology
- Microsoft® Windows® drivers
- USB connectivity
- Covered 100 card feeder (30 mil)
- 45 card output hopper (30 mil)
- Auto calibration of media
- Load-N-Go™ drop-in ribbon cartridge
- 16-character LCD display
- 300 dpi (11.8 dots/mm) print resolution
- 32 MB memory standard
- Two-year warranty on printer
- Two-year (unlimited passes) original printhead
- Kensington® physical lock slot

Optional Features

- CardSense™ single-card feed mode
- Built-in 10/100 Ethernet connectivity
- Lockable enclosure/card feeder and obscured output hopper
- ZebraCare™ extended warranty programs

Encoding Options & Specifications

- Magnetic stripe encoder—ISO 7811 (new and re-encoded, tracks 1, 2, and 3, high and low coercivity, stripe down, 30 mil card thickness)
- Smart card contact station—ISO 7816
- Combined MIFARE® contactless ISO 14443 and ISO 7816 contact encoder—PC/SC and EMV level 1 compliant

Bar Codes & Fonts

- Code 39, Code 128 B & C with & without check digit
- 2 of 5 Interleaved
- UPC-A, EAN 8 & EAN 13
- PDF417 2-D bar code and other symbologies can be printed via Windows drivers
- TrueType® and other symbologies available via Windows driver

Software

Microsoft Windows Certified Printer Drivers Supported

Windows XP, *Windows Vista®, Windows Server® 2003, *Windows Server 2008, *Windows 7

**32 bit and 64 bit compatible*

Supplies Specifications

- Zebra ix Series intelligent technology for authenticating and automating color ribbons
- Media Starter Kits—includes one (YMCKO or YMCKOK) ribbon with cleaning roller, 200 30-mil cards (blank or magnetic stripe)
- Cleaning supplies

True Colours ix Series High-Performance Ribbons

- YMCKO: 200 images/roll
- YMCKOK: 165 images/roll
- ½ Panel YMC Full KO: 250 images/roll
- Monochrome: black, blue, green, gold, silver, red 1000 images/roll; white 850 images/roll
- KdO: 500 images/roll
- KR: 500 images/roll

Card Compatibility

- Card Thickness: 30 mil
- Card Size: CR-80 ISO 7810 format, Type ID-1, 2.12" x 3.38" (54 x 86 mm)
- Card Material: PVC and composite
- Smart card contact—ISO 7816-1,2,3,4
- Smart card contactless MIFARE ISO 14443 A/B

Communications Interfaces

- USB V2.0—standard (cable included)
- Built-in 10/100 Ethernet—optional

Electrical

- Single-phase AC power
- 90V~264V AC RMS and 47-63 HZ (50-60 Hz nominal)
- FCC Class A

Physical

- Width: 7.9"/201 mm
- Height: 9.3"/236 mm
- Depth: 14.5"/368 mm
- Weight (printer only): 12.2 lbs/5.53 kg

Environmental

- Operating Temperature: 60° F/15° to 86° F/30° C
- Storage Temperature: 23° F/-5° C to 158° F/70° C
- Operating Humidity: 20% to 65% inclusive, non-condensing
- Storage Humidity: 20% to 70% inclusive, non-condensing

Genuine Zebra™ Supplies

Genuine Zebra supplies meet stringent quality standards and are recommended for optimal printing quality and proper printer performance. The ZXP Series 3 card printer is designed to work only with Zebra True Colours ix Series high-performance ribbons.

For more information, visit www.zebra.com

CardStudio™ Software

Zebra's ZMotif™ CardStudio™ is an easy-to-learn, easy-to-operate professional card design and card issuance software suite. It makes designing and printing professional photo ID cards and other cards easy, with basic to advanced features, and support for all Zebra card printers.



For more information, visit www.zebra.com/cardstudio

*Specifications subject to change without notice.

©2011 ZIH Corp. All product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic and True Colours are registered trademarks of ZIH Corp. All rights reserved. Microsoft, Windows, Windows Vista and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. MIFARE is a registered trademark of Philips Semiconductors Gratkorn GmbH Ltd. TrueType is a registered trademark of Apple Computer, Inc. Kensington is a registered trademark of ACCO Brands Corporation. All other trademarks are the property of their respective owners.



Corporate Headquarters

+1 800 423 0442

Email: inquiry4@zebra.com

Asia-Pacific Headquarters

+65 6858 0722

Email: apacchannelmarketing@zebra.com

EMEA Headquarters

+44 (0)1628 556000

Email: mseurope@zebra.com

Latin America Headquarters

+1 847 955 2283

Email: inquiry4@zebra.com

Other Locations

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom **Asia Pacific:** Australia, China, Hong Kong, India, Japan, Malaysia, South Korea, Singapore, Thailand **Latin America:** Brazil, Florida (LA Headquarters in USA), Mexico **Africa/Middle East:** Dubai, South Africa